

TECHNICAL	DATA:
TECHNICAL	DATA

OPERATING VOLTAGE 100KV DC

- 1. FLANGE MATERIAL: S41009/D, S41009/E & S41009/AF ALUMINIUM ATERMINAL MATERIAL: ALL TYPES BRASS.
- 2. CONTACT CAVITY & TAPER MUST NOT BE FILLED WITH ANY PETROLIUM BASED OIL.
- 3. MATERIAL OF INSULATION IS CAPABLE OF CONTINUOUS IMMERSION IN SHELL DIALA B.G. OIL OR EQUIVALENT.

ACCESSORIES:

CABLE ASSEMBLY USED WITH THIS SOCKET TO HAVE

TERMINATION 100 KV EURO (R10 TYPE).

FLANGE TO BE USED T20051/A

8 27.11.09 QCN

S41009/D WITHOUT HOLES OR SHORTING PLATE S41009/E WITH Ø3.8x16.5 HOLES

S41009/AF WITH SHORTING PLATE (NOT SHOWN)

WARNING:

THIS SOCKET MUST ONLY BE FITTED BY A TRAINED PERSON SEE CABLE TERMINATION DATA SHEET DS 1007 FOR FITTING OF CABLE TERMINATION TO SOCKET.

1051012

ESSEX

Dandong Light Electric Co..Ltd Rm.1606 Jiadi Square, No.64, Binjiang Middle Rd, Zhenxing, Dandong, Liaoning China T:0415-6123232 F:0415-6123533

REVISIONS			S	DUE TO C	ONTINUING F	PRODUCT D	EVELOPMENT	ESSEX	X-RAY	RESERVES	THE RIGHT	то мо	DIFY D	DATA WITHOUT	NOTICE
	NO.	DATE	BY	DRAWN	APPROVED	DATE	ISSUE	SCALE		О мот то	BE REPRODU	CED IN W	HOLE O	R PART WITHOUT	
	5	11.05.01	PCN 1455	JDF		15.07.96	8		N.T.S.	PRIOR F	PERMISSION O	F ESSEX	X-RAY &	& MEDICAL EQUIP	MENT LTD.
	6	01.03.04	DCN 2000	TITLE	100KV	FURO ((R10) (FNFF	RATOR	R RECE	FPTACI	F	D	RAWING No.	
	7	14.02.07	2616 DCN	2	E:	SSEX F	PART N	_	1009	9		_		DS10	12