

THIS DATA SHEET IS FOR IDENTIFICATION PURPOSES ONLY. NOMINAL DIMENSIONS IN MM.

TECHNICAL DATA:	ACCESSORIES:	INSTALLATION:
TERMINATION:— NOMINAL OPERATING VOLTAGE 75KV DC - USING AN ESSEX X—RAY APPROVED RECEPTACLE CABLE LENGTH TOLERANCE +/- 100mm SOLID RESIN TERMINATION CABLE:— VOLTAGE WITHSTAND 100KV DC 30KV (RMS) AC TERMINATION RESIN FIRE RESISTANT TO UL—94 FOR FULL CABLE DATA SEE ESSEX CABLE DATA SHEET	LOCKING RING T20204/A SPLIT WASHER T20226 PIN REPLACEMENT KIT P00432 INSTALLATION GREASE P00075	WARNING: CABLE SHOULD ONLY BE FITTED BY A TRAINED PERSON. A SUITABLE HIGH VOLTAGE GREASE SHOULD BE APPLIED TO THE TERMINATION. ENSURE THAT THE TERMINATION IS FULLY INSERTED IN THE SOCKET BEFORE SECURING THE LOCKING RING.

ESSEX

Dandong Light Electric Co.,Ltd Rm.1606 Jiadi Square, No.64, Binjiang Middle Rd, Zhenxing, Dandong, Liaoning China T:0415-6123232 F:0415-6123533

	REVISION:	S	DUE TO C	ONTINUING	PRODUCT DI	EVELOPM	1EN7	r essex	X-RAY	RESERVES	THE R	IGHT T	О МС	ODIFY	DATA	WITHOUT	NOTICE		
NO.	DATE	BY	DRAWN	APPROVED	DATE	ISSUE		SCALE		© иот то	BE REPR	RODUCE	D IN W	WHOLE	OR PAR	T WITHOUT			
4	05.01.01	DCN 1408	JDF		17.09.96		7		N.T.S.	PRIOR F	PERMISSIO	ON OF E	ESSEX	X-RAY	AY & MEDICAL EQUIPMENT LTD.				
5	11.05.01	DCN 1455	TITLE											DRAWI	NG No.				
6	29.11.06	DCN 2583	O THE FORE TERMINATION ESSEN 2000										\Box	~ 10	$2 \cap$				
7	06.03.09	DCN 2905	(CABLE TYPE C2212)									\cup	<u>ں ا</u> ر	$\angle \cup$					