



THIS DATA SHEET IS FOR IDENTIFICATION PURPOSES ONLY. NOMINAL DIMENSIONS IN MM.

TECHNICAL DATA:	ACCESSORIES:	INSTALLATION:
<p>OPERATING VOLTAGE 75KV DC</p> <p>1. TERMINAL MATERIAL BRASS</p> <p>2. MATERIAL OF INSULATION IS CAPABLE OF CONTINUOUS IMMERSION IN SHELL DIALA B.G. OIL OR EQUIVALENT.</p>	<p>CABLE ASSEMBLY USED WITH THIS RECEPTACLE TO HAVE A STANDARD 75KV TERMINATION 3 PIN TYPE</p>	<p>WARNING:</p> <p>THIS SOCKET MUST ONLY BE FITTED BY A TRAINED PERSON SEE CABLE TERMINATION DATA SHEET DS 1020 FOR FITTING OF CABLE TERMINATION</p>

ESSEX

Dandong Light Electric Co.,Ltd
Rm.1606 Jiadi Square,No.64,Binjiang Middle Rd,
Zhenxing, Dandong, Liaoning China
T:0415-6123232
F:0415-6123533

REVISIONS			DUE TO CONTINUING PRODUCT DEVELOPMENT ESSEX X-RAY RESERVES THE RIGHT TO MODIFY DATA WITHOUT NOTICE					
NO.	DATE	BY	DRAWN	APPROVED	DATE	ISSUE	SCALE	© NOT TO BE REPRODUCED IN WHOLE OR PART WITHOUT PRIOR PERMISSION OF ESSEX X-RAY & MEDICAL EQUIPMENT LTD.
2	26.03.97	DCN 583	JDF		9.9.96	5	N.T.S.	
3	15.07.99	DCN 1049	TITLE 3 PIN 75KV RECEPTACLE ESSEX PART NO. S31008					DRAWING No. DS1021
4	11.05.01	DCN 1455						
5	19.04.06	DCN 2454						