



THIS DATA SHEET IS FOR IDENTIFICATION
PURPOSES ONLY. NOMINAL DIMENSIONS IN MM.

6 HOLES Ø7.00 EQUI-
SPACED ON 114.30 PCD

IMPORTANT: 3 HOLES M5x.08-6H 10.0 DEEP
IN S51007/A, S51007/E, S51028/A & S51038 ONLY

TECHNICAL DATA:			ACCESSORIES:					INSTALLATION:				
OPERATING VOLTAGE 160KV DC 1. FLANGE MATERIAL S51007, S51007/A & S51028/A BRASS BRIGHT NICKEL PLATED. S51007/D, S51007/E, S51038 ALUMINIUM. TERMINAL MATERIAL ALL TYPES BRASS. 2. CONTACT CAVITY & TAPER MUST NOT BE FILLED WITH ANY PETROLIUM BASED OIL. 3. MATERIAL OF INSULATION IS CAPABLE OF CONTINUOUS IMMERSION IN SHELL DIALA B.G. OIL OR EQUIVALENT. EPOXY RESIN COLOUR ALL TYPES GREY			CABLE ASSEMBLY USED WITH THIS SOCKET TO HAVE TERMINATION 160 KV EURO (R24 TYPE). FLANGE TO BE USED T20131/A S51007 WIDE BAND CONTACTS S51007/A WIDE BAND CONTACTS & TAPPED HOLES S51007/D WIDE BAND CONTACTS S51007/E WIDE BAND CONTACTS & TAPPED HOLES S51028/A WITH TAPPED HOLES S51038 WITH TAPPED HOLES					WARNING: THIS SOCKET MUST ONLY BE FITTED BY A TRAINED PERSON SEE CABLE TERMINATION DATA SHEET DS 1002 FOR FITTING OF CABLE TERMINATION TO SOCKET.				
<div>ESSEX</div> <div>Dandong Light Electric Co.,Ltd Rm.1606 Jiadi Square,No.64,Binjiang Middle Rd, Zhenxing, Dandong, Liaoning China T:0415-6123232 F:0415-6123533</div>			REVISIONS			DUE TO CONTINUING PRODUCT DEVELOPMENT ESSEX X-RAY RESERVES THE RIGHT TO MODIFY DATA WITHOUT NOTICE						
			NO.	DATE	BY	DRAWN	APPROVED	DATE	ISSUE	SCALE	© NOT TO BE REPRODUCED IN WHOLE OR PART WITHOUT PRIOR PERMISSION OF ESSEX X-RAY & MEDICAL EQUIPMENT LTD.	
			4	01.03.04	DCN 2000	MGM		07.07.98	7	N.T.S.		
			5	27.02.06	DCN 2432	TITLE 160KV (R24) EURO GENERATOR RECEPTACLES ESSEX PART NO. AS DETAILED						
			6	14.02.07	DCN 2616							
7	21.02.08	DCN 2752	DRAWING No. DS1030									