



THIS DATA SHEET IS FOR IDENTIFICATION  
PURPOSES ONLY – NOMINAL DIMENSIONS IN MM.

TECHNICAL DATA:	ACCESSORIES:	INSTALLATION:
<p>TERMINATION:–</p> <p>NOMINAL OPERATING VOLTAGE 160KV DC CABLE LENGTH TOLERANCE +/- 100mm</p> <p>CABLE:– VOLTAGE WITHSTAND 160KV DC</p> <p>FOR FULL CABLE DATA SEE ESSEX CABLE DATA SHEET</p>		<p>WARNING:</p> <p>CABLE SHOULD ONLY BE FITTED BY A TRAINED PERSON. CABLE CAN RETAIN ELECTRICAL CHARGE. DISCHARGE TO EARTH BEFORE HANDLING. A SUITABLE HIGH VOLTAGE GREASE SHOULD BE APPLIED TO THE TERMINATION.</p> <p>ENSURE THAT THE TERMINATION IS FULLY INSERTED IN THE SOCKET BEFORE ADJUSTING. SEE DS1041 FOR FITTING INSTRUCTIONS.</p>

**ESSEX**

Dandong Light Electric Co.,Ltd  
Rm.1606 Jiadi Square,No.64,Binjiang Middle Rd,  
Zhenxing, Dandong, Liaoning China  
T:0415-6123232  
F:0415-6123533

REVISIONS

NO.	DATE	BY
2	10.05.01	DCN 1455

DUE TO CONTINUING PRODUCT DEVELOPMENT ESSEX X-RAY RESERVES THE RIGHT TO MODIFY DATA WITHOUT NOTICE

DRAWN	APPROVED	DATE	ISSUE	SCALE
TSC		07.06.00	2	1:2

© NOT TO BE REPRODUCED IN WHOLE OR PART WITHOUT  
PRIOR PERMISSION OF ESSEX X-RAY & MEDICAL EQUIPMENT LTD.

TITLE  
160KV SPRING LOADED ASSEMBLY WITH SPRING SUPPORT  
(CABLE TYPE C2042)

DRAWING No.

DS1047