



THIS DATA SHEET IS FOR IDENTIFICATION  
PURPOSES ONLY. NOMINAL DIMENSIONS IN MM.

TECHNICAL DATA:	ACCESSORIES:	INSTALLATION:
<p>OPERATING VOLTAGE 225KV DC</p> <p>1. FLANGE MATERIAL S71001, S71001/F BRASS BRIGHT NICKEL PLATED. S71001/A, S71001/AF ALUMINIUM TERMINAL MATERIAL ALL TYPES BRASS</p> <p>2. CONTACT CAVITY AND TAPER MUST NOT BE FILLED WITH ANY PETROLEUM BASED OIL.</p> <p>3. MATERIAL OF INSULATION IS CAPABLE OF CONTINUOUS IMMERSION IN SHELL DIALA B.G. OIL OR EQUIVALENT.</p>	<p>CABLE ASSEMBLY USED WITH THIS SOCKET TO HAVE TERMINATION 225KV (R28 TYPE)</p> <p>SUITABLE FLANGES: T20405 T20289</p> <p>S71001/F WITH SHORTING PLATE S71001/AF WITH SHORTING PLATE</p>	<p>WARNING: THIS SOCKET MUST ONLY BE FITTED BY A TRAINED PERSON. SEE CABLE TERMINATION DATA SHEET DS1041 FOR FITTING OF CABLE TERMINATION TO SOCKET.</p>

**ESSEX**

Dandong Light Electric Co.,Ltd  
Rm.1606 Jiadi Square,No.64,Binjiang Middle Rd,  
Zhenxing, Dandong, Liaoning China  
T:0415-6123232  
F:0415-6123533

REVISIONS			DUE TO CONTINUING PRODUCT DEVELOPMENT ESSEX X-RAY RESERVES THE RIGHT TO MODIFY DATA WITHOUT NOTICE						
NO.	DATE	BY	DRAWN	APPROVED	DATE	ISSUE	SCALE	© NOT TO BE REPRODUCED IN WHOLE OR PART WITHOUT PRIOR PERMISSION OF ESSEX X-RAY & MEDICAL EQUIPMENT LTD.	
2	14.02.07	DCN 2616	MGM		16.11.05	2	N.T.S.		
			TITLE 225KV (R28) GENRATOR RECEPTACLE ESSEX PART NO. S71001						DRAWING No.  DS1070

DRAWING No.

DS1070