



THIS DATA SHEET IS FOR IDENTIFICATION
PURPOSES ONLY. NOMINAL DIMENSIONS IN MM.

TECHNICAL DATA:

ACCESSORIES:

INSTALLATION:

OPERATING VOLTAGE 75KV DC

1. TERMINAL MATERIAL BRASS
2. MATERIAL OF INSULATION IS CAPABLE OF CONTINUOUS IMMERSION IN SHELL DIALA B.G. OIL OR EQUIVALENT.

CABLE ASSEMBLY USED WITH THIS RECEPTACLE TO HAVE
A STANDARD 75KV TERMINATION 3 PIN TYPE

WARNING:
THIS SOCKET MUST ONLY BE FITTED BY A TRAINED
PERSON SEE CABLE TERMINATION DATA SHEET
DS 1020 FOR FITTING OF CABLE TERMINATION

ESSEX

Dandong Light Electric Co.,Ltd
Rm.1606 Jiadi Square,No.64,Binjiang Middle Rd,
Zhenxing, Dandong, Liaoning China
T:0415-6123232
F:0415-6123533

REVISIONS			DUE TO CONTINUING PRODUCT DEVELOPMENT ESSEX X-RAY RESERVES THE RIGHT TO MODIFY DATA WITHOUT NOTICE						© NOT TO BE REPRODUCED IN WHOLE OR PART WITHOUT PRIOR PERMISSION OF ESSEX X-RAY & MEDICAL EQUIPMENT LTD.
NO.	DATE	BY	DRAWN	APPROVED	DATE	ISSUE	SCALE		
2	08.10.08	DCN 2843	MGM		16.06.08	2	N.T.S.		
			TITLE						DRAWING No.
			3 PIN 75KV RECEPTACLE						DS1073
			ESSEX PART NO. S31008/B						