LOCKING RING 2.5"-20UN-2A THD-	CONTA	ACT PINS TO FIT Ø4mm HOLE	LOCKING RING 2.5"-20UN-2A THD-
8.1	$\overline{\ }$	-REF LENGTH 8.1	129 REF LENGTH
THE REMOVABLE PINS		TEMOVABLE PIN	S REMOVABLE OF
		1±0.381	SPLIT COLLAR WHEN REMOVED MAX DIA 40mm ESSEX PART NUMBERS A36007/XXM – 3 PIN CABLE TYPE C2214
Ø35 Ø55.7			THIS DATA SHEET IS FOR IDENTIFICATION PURPOSES ONLY. NOMINAL DIMENSIONS IN MM.
TECHNICAL DATA:		ACCESSORIES:	INSTALLATION:
TERMINATION: NOMINAL OPERATING VOLTAGE 75KV CABLE LENGTH TOLERANCE +/- 100mm SOLID RESIN TERMINATION. CABLE: VOLTAGE WITHSTAND 75KV DC 25KV (RMS) AC FOR FULL CABLE DATA SEE ESSEX CABLE DATA SHEET		ACEMENT KIT P00432 ION GREASE P00075	WARNING: CABLE SHOULD ONLY BE FITTED BY A TRAINED PERSON. CABLE CAN RETAIN ELECTRICAL CHARGE. DISCHARGE TO EARTH BEFORE HANDLING. A SUITABLE HIGH VOLTAGE GREASE SHOULD BE APPLIED TO THE TERMINATION. ENSURE THAT THE TERMINATION IS FULLY INSERTED IN THE SOCKET BEFORE SECURING THE LOCKING RING. AFTER INSTALLATION FULLY TIGHTEN LOCKING RING TO PREVENT UNAUTHORISED DISCONNECTION.
	ISIONS		X-RAY RESERVES THE RIGHT TO MODIFY DATA WITHOUT NOTICE
Dandong Light Electric Co.,Ltd	TE BY	DRAWN APPROVED DATE ISSUE SCALE MGM 11.02.10 1	N.T.S. NOT TO BE REPRODUCED IN WHOLE OR PART WITHOUT PRIOR PERMISSION OF ESSEX X-RAY & MEDICAL EQUIPMENT LTD.
Rm.1606 Jiadi Square,No.64,Binjiang Middle Rd, Zhenxing, Dandong, Liaoning China T:0415-6123232 F:0415-6123533		TITLE 3 PIN 75KV TERMINATION RE TO 3 PIN 75KV TERMINATION	EMOVABLE FLANGE