



THIS DATA SHEET IS FOR IDENTIFICATION  
PURPOSES ONLY - NOMINAL DIMENSIONS IN MM.

#### TECHNICAL DATA:

TERMINATION:-  
NOMINAL OPERATING VOLTAGE 210KV DC  
- USING AN ESSEX X-RAY APPROVED RECEPTACLE  
CABLE LENGTH TOLERANCE +/- 100mm

CABLE:- VOLTAGE WITHSTAND 250KV DC  
75KV (RMS) AC

FOR FULL CABLE DATA SEE ESSEX CABLE DATA SHEET

#### ACCESSORIES:

CLAMPING SLEEVES:-  
STANDARD FLANGE T22341

INSTALLATION GREASE P00075

#### INSTALLATION:

WARNING:

CABLE SHOULD ONLY BE FITTED BY A TRAINED PERSON.  
CABLE CAN RETAIN ELECTRICAL CHARGE.  
DISCHARGE TO EARTH BEFORE HANDLING.  
OIL MUST NOT BE USED ON THE RUBBER TERMINATION, ONLY SUITABLE  
HIGH VOLTAGE GREASE.  
ENSURE BY ADJUSTING THE CLAMPING SLEEVE THAT WHEN THE  
TERMINATION IS FULLY INSERTED IN THE SOCKET THERE IS A  
GAP OF 6mm BETWEEN THE MATING FACES OF THE CLAMPING SLEEVE  
AND SOCKET BEFORE TIGHTENING THE CLAMPING SLEEVE.

# ESSEX

Dandong Light Electric Co.,Ltd  
Rm.1606 Jiadi Square,No.64,Binjiang Middle Rd,  
Zhenxing, Dandong, Liaoning China  
T:0415-6123232  
F:0415-6123533

#### REVISIONS

NO.	DATE	BY

DUE TO CONTINUING PRODUCT DEVELOPMENT ESSEX X-RAY RESERVES THE RIGHT TO MODIFY DATA WITHOUT NOTICE

DRAWN	APPROVED	DATE	ISSUE	SCALE
MJT		06.01.12	1	N.T.S.

© NOT TO BE REPRODUCED IN WHOLE OR PART WITHOUT  
PRIOR PERMISSION OF ESSEX X-RAY & MEDICAL EQUIPMENT LTD.

#### TITLE

210 SEIFERT SPRING LOADED (R30 TYPE)  
RIGHT ANGLE (CABLE TYPE C2236)

DRAWING No.

DS1087