



THIS DATA SHEET IS FOR IDENTIFICATION
PURPOSES ONLY - NOMINAL DIMENSIONS IN MM.

TECHNICAL DATA:

TERMINATION:-

NOMINAL OPERATING VOLTAGE 225KV DC -
USING AN ESSEX X-RAY APPROVED RECEPTACLE

CABLE LENGTH TOLERANCE +/- 100mm

CABLE:- VOLTAGE WITHSTAND 250KV DC, 75KV AC (RMS)

FOR FULL CABLE DATA SEE ESSEX CABLE DATA SHEET

ACCESSORIES:

CLAMPING SLEEVES:-

STANDARD FLANGE T20405

INSTALLATION GREASE P00075

INSTALLATION:

WARNING:

CABLE SHOULD ONLY BE FITTED BY A TRAINED PERSON.
CABLE CAN RETAIN ELECTRICAL CHARGE.
DISCHARGE TO EARTH BEFORE HANDLING.
A SUITABLE HIGH VOLTAGE GREASE SHOULD BE
APPLIED TO THE TERMINATION.

ENSURE THAT THE TERMINATION IS FULLY INSERTED
IN THE SOCKET BEFORE ADJUSTING.
SEE DS1041 FOR FITTING INSTRUCTIONS.

ESSEX

Dandong Light Electric Co.,Ltd
Rm.1606 Jiadi Square,No.64,Binjiang Middle Rd,
Zhenxing, Dandong, Liaoning China
T:0415-6123232
F:0415-6123533

REVISIONS

NO.	DATE	BY

DUE TO CONTINUING PRODUCT DEVELOPMENT ESSEX X-RAY RESERVES THE RIGHT TO MODIFY DATA WITHOUT NOTICE

DRAWN	APPROVED	DATE	ISSUE	SCALE
MJT		28.02.12	1	1:2

© NOT TO BE REPRODUCED IN WHOLE OR PART WITHOUT
PRIOR PERMISSION OF ESSEX X-RAY & MEDICAL EQUIPMENT LTD.

TITLE
225KV SPRING LOADED ASSEMBLY WITH RIGHT ANGLE
(CABLE TYPE C2236)

DRAWING No.
DS1091